

Speedo Quick-Release Couplings and Nozzle Holders

SPEEDO quick-release couplings and nozzle holders have internal grip rings and are externally fitted.

Threaded Quick-Released Couplings (Ductile Steel)			Blasthose Quick-Released Couplings (Ductile Steel)	
For Pipe-size Diameter	Part #		Fit Blasthose Outer Diameter	Part #
1/2" NPS	0633-004/A*		27mm	0042-004/A*
1-1/4" NPS	0633-007/D		39mm	0042-039/D
1-1/2" NPS	0633-008/D		48mm	0042-048/D
2" NPS	0633-009/D		56mm	0042-056/D
Part # 0673-005 3/4" Rubber Gasket fits 0633-004/A & 0042-004/A			Nylon blasthose couplings available upon request	
Part # 0673-007 1-1/4" Rubber Gasket fits all other sizes of quick-released couplings		* Offered only in Aluminum		

Aluminum Nozzle-Holders		
Fit Blasthose Outer Diameter	Fine Thread Part #	Wide Thread Part #
27mm	0052-527	-
39mm	0052-539	0052-639 or 0052-639/N
48mm	0052-548	0052-648 or 0052-648/N
56mm	0052-556	0052-656
Part # 0083-053 Nozzle Washer for 48mm and 56mm holders		
Nylon nozzle holders available		



Tungsten Carbide Blast Nozzles



3/4" NPSM STRAIGHT BORE SHORT NOZZLES

Suitable for use in small pressure blast machines, blast cabinets, and internal pipe blasting equipment.

Part #	Size	Part #	Size
0052-002	Ø 3.2 X 45mm	0052-005	Ø 8.0 X 45mm
0052-003	Ø 4.8 X 45mm	0052-006	Ø 9.5 X 45mm
0052-004	Ø 6.3 X 45mm	0052-008	Ø 13.0 X 45mm



1-1/4" NPSM ANGLE NOZZLES

Ideal for cleaning hard-to-reach areas and are available with one, two, or three outlets.

Part #	No. of outlets	Bore Diameter	Length
0052-022	3	3.2mm	80mm
0052-023	3	4.8mm	80mm
0052-024	3	6.0mm	80mm
0052-025	3	8.0mm	80mm
0052-026	3	9.0mm	80mm
0052-026/1	1	9.0mm	80mm



LONG VENTURI NOZZLES

Now accepted as the industry standard, these are widely used for high production blasting as they provide excellent durability and wear resistance. These are available in aluminium jackets.

1-1/4" NPSM Fine Thread	50mm Wide Thread	Length	Orifice Size
0052-134	0052-124	135mm	6.3mm (1/4")
0052-135	0052-125	145mm	8.0mm (5/16")
0052-136	0052-126	170mm	9.5mm (3/8")
0052-137	0052-127	200mm	11.0mm (7/16")
0052-138	0052-128	230mm	13.0mm (1/2")

